

Volt ⚡ electronic

Www.voltelectronic.com

فروشگاه آنلاین قطعات الکترونیک

ایران-تهران، خیابان جمهوری، پاساژ توکل، طبقه اول واحد ۱۱۵



0935-8181438

0991-5800191

021- 66 77 71 10



0912-5800191 کوششی

0912-4175185 عروجلو



voltelectronic.shop



Www.voltelectronic.com



No: 115 First floor, Tavakol Bldg
Jomhoori Ave, Tehran-IRAN


Single Port RJ45 Connector
with Magnetics Module and LED

Part Number


HR911105A (Shield Type: A)

- Designed for Network Interface Card Application
- Meets or Exceeds IEEE802.3 standards including 350uH Min OCL with 8mADC
- High performance for EMI suppression, Crosstalk, Return Loss and Consistent Electrical
- Minimum 1500Vrms isolation per IEEE802.3 requirement
- Minimize PCB space and Simplify PCB Layout
- Less magnetic components to place on PCB, Higher reliability and yields


Mechanical Dimensions:




(Bottom View)



(Side View)



(Comp Side View)



(Front View)

Right LED
Yellow LED

Left LED
Green LED

Part No.: HR911105A	Unless otherwise specified, Tolerance:	Rev: A	DRWN:	Date:
Dimensions in mm	.xx ± 0.25	Page 1/1	APPD:	Date:

Single Port RJ45 Connector
with Integrated Magnetics and LED
for 10/100Base-TX NIC Applications

Part Number:

HR911105

Electrical Specification @25°C

Isolation: 1500Vrms (UTP Side to Chip Side)

OCL: 350uH Minimum @100KHz 100mV with 8mADC

Insertion Loss: -1.0dB Maximum @300KHz ~ 100MHz

Return Loss: -20dB Minimum @1MHz ~ 10MHz

-16dB Minimum @10MHz ~ 30MHz

-12dB Minimum @30MHz ~ 60MHz

-10dB Minimum @60MHz ~ 80MHz

Common Mode Rejection: -30dB Minimum @1MHz ~ 50MHz


-20dB Minimum @50MHz ~ 150MHz

Crosstalk: -40dB Minimum @1MHz ~ 30MHz

-35dB Minimum @30MHz ~ 60MHz

-30dB Minimum @60MHz ~ 100MHz

Schematics



Notes: Connect CHS GND to PCB Ground

Part No.: HR911105	Unless otherwise specified, Tolerance:	Rev: A	DRWN:	Date:
Dimensions in mm	.xx ±0.25	Page 1/1	APPD:	Date:
Tel: (0760) 2121067 2121679 • Fax: (0760) 2121065 • E-Mail: hanrun@pub.zhongshan.gd.cn • http: www.hanrun.com				